(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 24 June 2004 (24.06.2004)

PCT

(10) International Publication Number WO 2004/052739 A1

- (51) International Patent Classification7: 19/38. B25J 19/04
- B65D 19/31.
- (21) International Application Number:

PCT/AU2003/001652

(22) International Filing Date:

10 December 2003 (10.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002953248

10 December 2002 (10.12.2002) ΑU

2002953466

20 December 2002 (20.12.2002) AU

- (71) Applicant (for all designated States except US): BRAM-BLES AUSTRALIA LIMITED [AU/AU]; Level 40 Gateway, 1 Macquarie Place, Sydney, New South Wales 2000 (AU).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LUCAS, Michael, David [AU/AU]; Unit 12L 175 Gibbes St., Chatswood, New South Wales 2067 (AU). TOWNSEND, Steve [AU/AU]; Unit 12L 175 Gibbes St., Chatswood, New South Wales 2067 (AU).


- (74) Agent: MOLINS, Michael; Level 25, Chifley Tower. 2 Chifley Square, Sydney, New South Wales 2000 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AUTOMATED PALLET INSPECTION AND REPAIR



(57) Abstract: An automatic pallet inspection cell (10) comprises one or two multi axis robot arms (14, 15) which terminate in either internal or exterior pallet grippers. The robots are used to transport a gripped pallet (12) through an automated inspection station (16) which compiles a three dimensional data map of a pallet surface. A processor interprets the map and producing a recipe for the robot or robots. One or more stations (17, 18, 19) conduct pallet repair operations that are specified by the recipe. A method for levelling a pallet prior to board removal by a band saw (17) is also disclosed, characterised by rolling the pallet relative to a blade of the band saw to a first and a second roll angle, and positioning the pallet at a position which is an average of the first and second roll angles.

